



016-QMS

SW 1500 (S) & SW 3000 (D)
Welding Fume Extractor/Filter Unit

SW 1500 (S) & SW 3000 (D) Welding Fume Extractor/ Filter Unit

Welding fume extractor is exclusively designed for fume/dust from welding, laser, plasma cutting in industrial applications.

- Flexible arm is equipped with 360 degree rotating and length of 3 metres.
- High filtration efficiency.
- Easy to position in application areas.
- Equipped with three layered filter system to avoid the effect of flame with safer, durable and more reliable.
- It can suck exactly from the source which makes best fume collection efficiency.



Technical Specifications

Model	Units	SW 1500 (S)	SW 3000 (D)
Power	KW / HP	1.5/2	3/4
Voltage	V	400	400
Frequency	Hz	50	50
Max. Airflow	m ³ /hr	1500	3000
Max. Arm Length	Mtrs	3	2 x 3
Phase	-	3 Phase	3 Phase
Filter Type	-	PTFE Cartridge	PTFE Cartridge
Filter Surface Area	sq. m	10	20
Filter Cleaning System		Automatic Pulse Jet Cleaning	Automatic Pulse Jet Cleaning
Filter Efficiency		99.97%	99.97%
Noise Level	dbA	72	75